

TIM-GAP P-61

Thermally Conductive Silicone Gap Filler Putty Sheets

DESCRIPTIONS

TIM-GAP P-61 is very soft Putty Type, highly conformable thermal interface gap filler designed to meet industry's rapidly growing need for interface material with high thermal conductivity and conformability for low stress applications.

TIM-GAP P-61 is designed with flame retardant silicone polymer filled with thermally conductive fillers for wide range of applications. It will provide superb protection against damage due to deformation as well as shock or vibration.

KEY FUTURES AND BENEFITS

- **High Thermal Conductivity (6.1 W/m-k)**
- **Cost-Effective Solution**
- Soft, low stress on component
- Clean and easy to apply

APPLICATIONS

- Interface for semiconductors requiring low pressure or spring clamp mounting
- Graphic chips to heat sinks
- Mass storage drives

AVAILABILITY

Available Thickness (mm): 1.5, 2.0, 2.5
Available Configurations: Sheet form (200mm x 300mm) and die-cut parts

Typical Property	Test Method	Value
Color	Visual	Reddish/Gray
Specific Gravity, @ 25°C	ASTM D792	3.1
Hardness (Shore 00)	ASTM D2240	Gel Type
Flammability	UL 94	V-0 Equivalent
Operating Temperature Range.		-55°C to 150°C
THERMAL		
Thermal Conductivity (W/m-K)	ASTM D5470	6.1
Thermal Resistance (°C-in ² /w)(14psi, 1.5mm thickness)	ASTM D5470	0.45
ELECTRICAL		
Breakdown Voltage (KV/mm)	ASTM D149	12
Dielectric Constant (1KHz)	ASTM D149	7.2
Dissipation Factor (1KHz)	ASTM D150	0.02
Volume Resistivity (Ohm-m)	ASTM D257	1 x 10 ¹²

DISCLAIMER: All statements, technical information, and recommendations related to Timtronics products are based on information believed to be reliable, but accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You must assume all risks and liability associated with such use. Timtronics will not be liable for any indirect, special, incidental or consequential loss or damage arising from this product, regardless of legal theory asserted.